



Typical Inspection Data:

Density @ 20°C	1.124 g/cm ³
Appearance	Blue liquid
Boiling Point	168°C

Protection Levels:

Super Coldmaster (%)	Approx. Protection (°C)
33	-18
50	-36
60	-52

Super Coldmaster Concentrate

Recommended by Comma for applications requiring:

- Conforms to: BS6580:2010; AFNOR NFR 15-601

Product Features:

- A Mono Ethylene Glycol (MEG) based engine coolant / anti-freeze concentrate.
- Suitable for use in all types of vehicle requiring an MEG coolant.
- Suitable for Ferrous and Aluminium engines.
- 2 years full protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.

Directions for use:

- Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
- Pour into vehicle cooling system.
- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

Handling:

- Remove spills from paintwork immediately.
- Keep away from foodstuffs and oxidising agents.
- Store in airtight container.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

20-11-2014