

# FAVORIT

## Technical Data Sheet

### Favorit Premium DPF SAE 5W-30 API SN/CF



#### Packages:

1L, 4L, 5L, 20L, 60L, 208L

#### Meets the requirements and specifications:

SAE 5W-30

API SN/CF

ACEA C3

MB 229.1

GM dexos2

VW 505.01/505.00/502.00

#### Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm <sup>2</sup> /c at 40 °C	STB ISO 3104-2003	58,09
Kinematic viscosity mm <sup>2</sup> /c at 100 °C	STB ISO 3104-2003	10,14
Viscosity index	STB 1797	163
Flash point, °C	GOST 4333	224
Pour point, °C	GOST 20287	-40
TBN, g KOH/kg	GOST 11362	7,8
Density at 20°C, kg/m <sup>3</sup>	GOST 3900	851,9

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.  
Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.  
Показатели могут варьироваться в пределах допустимой нормы.

LLC "Eurasia Lubricants"

223034, Republic of Belarus, Minsky region, Zaslavl, Zavodskaya str. 1, room 3