

## **Technical Data Sheet**

## Favorit Pro Energy SAE 0W-20 API SN/CH-4



Packages: 1L, 4L, 5L, 20L, 60L, 208L

Meets the requirements and specifications:
API SN/CH-4 ILSAC GF-5 GM dexos1

**[EN] Favorit Pro Energy SAE 0W-20 API SN/CH-4** multigrade, fully synthetic engine oil designed for modern gasoline and turbodiesel engines. Provides exceptional viscosity and superior engine lubrication at start-up, even at very low temperatures. It has high washing properties and excellent thermo-oxidative stability.

[RU] Favorit Pro Energy SAE 0W-20 API SN/CH-4 всесезонное полностью синтетическое моторное масло, разработанное современных бензиновых ДЛЯ турбодизельных Обеспечивает двигателей. исключительную текучесть и превосходную смазку двигателя при запуске, даже при очень температурах. Обладает высокими моющими свойствами и прекрасной термоокислительной стабильностью.

**Precautions:** Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

**Storage conditions:** Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

## **Product Characteristics:**

| Name of indicator                                | <b>Test methods</b> | Value  |
|--------------------------------------------------|---------------------|--------|
| Kinematic viscosity mm <sup>2</sup> /c at 40 °C  | STB ISO 3104-2003   | 40,6   |
| Kinematic viscosity mm <sup>2</sup> /c at 100 °C | STB ISO 3104-2003   | 7,82   |
| Viscosity index                                  | STB 1797            | 167,01 |
| Flash poin, °C                                   | GOST 4333           | 224    |
| Pour point, °C                                   | GOST 20287          | -42    |
| TBN, g KOH/kg                                    | GOST 11362          | 7,1    |
| Density at 20°C, kg/m3                           | GOST 3900           | 837    |

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range. Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные. Показатели могут варьироваться в пределах допустимой нормы.